

Disclosure of Invention

“Significant Dust Enhancement Over Land and Ocean”

**Steven D. Miller
Naval Research Laboratory
Monterey, CA 93943-5502**

a) Purpose

The purpose of the Land/Ocean Significant Dust Enhancement Product is to provide an indication of the horizontal distribution of airborne dust over both land water surfaces for daytime scenes. The regions of dust are enhanced as shades of pink, depending on opacity, against darker non-dust backgrounds.

b) Background

A recent study (R. Cantu; “The Role of Weather in Major Naval Aviation Mishaps”, MS Thesis, 106 pp., NPS Monterey) has indicated that poor visibility has factored into approximately 54% of Navy aircraft “Class-A” mishaps, for an estimated annual loss of \$51 million. Of these mishaps it was reported that 56% were preventable had better forecasting and/or observational tools been available. The current Dust Enhancement Product represents a paradigm shift in the way dust is observed from the space platform, and is directly applicable to mitigating this multi-million dollar liability.

c) Description and Operation

As presented, the Dust Enhancement Product is actually a combination of two independent enhancement algorithms—one applicable to water backgrounds and the other to land backgrounds. Miller and Lee (AMS 11th Satellite Meteorology Conference; October 2001, Madison WI, pp. 43-46) and Miller (NRL Formal Report; 2002, Accepted) provide a comprehensive discussion of the ocean-component of the Dust Enhancement Product as applied to the Sea-viewing Wide Field-of-view Sensor (SeaWiFS) instrument (these publications have been attached to this application). It is based physically on the premise that silicate aerosols preferentially absorb blue light compared to green and red light, whereas cloud particles (liquid or ice) are more or less non-absorbing across this region and reflect all three components strongly. Therefore, a spectral difference between red and blue light will be much larger for dust than for clouds. In this way, data from a radiometer with spectral resolution capable of measuring the red, green, and blue components of reflected solar energy can be combined to further enhance and decouple the dust signal from clouds. The spectral difference is normalized by the magnitude of the reflectance such that additional sensitivity to thin (low reflectance) dust is achieved. The approach requires correction of the multi-channel data to remove scattering contamination from the molecular atmosphere prior to computing the enhancement.

No literature discussing the over-land component of the current Dust Enhancement Product has been drafted to date, although a submission to the peer-review literature on the topic is planned. A PowerPoint presentation, providing an overview of the method as applied to the Moderate Resolution Imaging Spectroradiometer (MODIS, aboard the Earth Observing System Terra satellite) and examples, is available upon request. Because the land background possesses similar spectral properties to the airborne dust at visible/shortwave-infrared wavelengths, the simple ocean-component described above is insufficient for identifying dust over land. We must instead appeal to thermal contrast and spectral property differences, which require channels in the infrared part of the spectrum. With its 36 narrowband channels spanning the optical portion of the electromagnetic spectrum from 0.4 to 14.4 micrometers, MODIS is well equipped to exploring these techniques from a single platform (although the Dust Enhancement Product may be achieved by combining registered data from a collection of independent platforms).

Three factors contribute to the over-land Dust Enhancement Product, and are outlined as follows: During the day, cooler emissions from an elevated dust layer contrast against the warm emissions from a heated surface. The same temperature signature holds true for clouds, but the same spectral decoupling applied to the over-ocean enhancement applies also to clouds over land. Combining the temperature and shortwave-differences provides a means to detecting the optically thick portion of the dust plume. Optically thin regions of dust will not produce a strong infrared temperature depression. However, spectral differences in thermal (11.0 – 12.0 micrometers) transmission for dust are very useful in determining areas of thin dust. The signature is opposite in sign to that of thin cirrus. Combining these multispectral features together yields a tractable algorithm for the enhancement of dust over land. Although the land and water enhancement algorithms differ significantly, the land enhancement has been formulated such that dust over land is the same hue (shades of pink) as dust over water with minimal discontinuity in saturation across coastal boundaries.

d) Advantages and New Features

The primary advantage of the Dust Enhancement Product is its ability to call immediate attention to areas where there airborne dust resides, often in regions where even the true color imagery experiences difficulty in discerning. The enhancement highlights mesoscale circulations in optically thin dust, and is also useful for identifying volcanic plumes (e.g., Mt. Etna 7/26/01 eruption—image attached). The latter capability is of particular relevance to both military and civilian aviation. The algorithm is applicable to a wide range of ocean color instruments in the ocean-only mode (i.e., true color over land surfaces) or in the ocean/land mode provided infrared information is available either on the same platform or co-registered with temporally close imagery from an independent platform.

e) Alternatives

Alternative methods exist for enhancing dust over land and water. Panchromatic (black/white) imagery with scaling thresholds chosen to enhance a small dynamic range

of temperature or reflectance values has been applied to visible and infrared geostationary imagery. The resultant enhancement appearance, usually only of marginal quality, is highly dependent on the thresholds chosen and hence not suitable for operations. Combinations of single-channel visible and infrared data is a marked improvement over the scaling described above, but still suffers cloud/dust ambiguity for lack of multi-channel visible data (i.e., the basis for the over-ocean Dust Enhancement Product which requires blue and short wave infrared channels). The Empirical Orthogonal Function (EOF, or sometimes referred to as "principle component") method has been shown to do a good job of enhancing dust over land and water. However, results produced by this method are highly dependent on the variability of the scene and hence will provide an inconsistent enhancement depending on background and dimension of the region. Contrast reduction, which takes advantage of the blurring affect of dust over otherwise sharp terrestrial features, has been applied successfully for dust detection over land, but naturally fails over ocean and also struggles in regions where terrain is less variable (e.g., desert plains, where dust incidentally is most common).

None of the above-mentioned methods enlists multi-channel visible data to take advantage of the inherent spectral variability of dust at these wavelengths. The unified land/ocean Dust Enhancement Product is a unique solution to the daytime dust detection problem. A comparison between the visible/infrared combination technique (applied here to Meteosat 5 data) and the current algorithm (applied to Terra-MODIS data) for a space and time co-located dust storm event in Southwest Asia is attached. The superior detection of dust by the current method over both land and water as demonstrated by these data are thought to be of immediate relevance to Navy METOC operations in several regions of the world that experience significant dust outbreaks (including Southwest Asia, Africa, the Mediterranean, and the West Pacific).

EXECUTIVE SUMMARY

INTRODUCTION

A new processing capability for true color, vegetation enhancement, and desert dust enhancement using imager data from the Sea-viewing Wide Field of View Sensor (SeaWiFS) has been developed for Naval meteorology/oceanography (MetOc) operations support. The data are captured via direct broadcast high-resolution picture transmission (HRPT) at Navy Regional Centers in Rota, Bahrain, and Yokosuka, and processed at the Naval Research Laboratory in Monterey. The raw data are calibrated, corrected for missing lines and clutter, corrected for molecular scatter contamination, and enhanced through multispectral combination to yield value added products. The processing has been automated completely such that products, generated upon receipt of data, are hosted upon a password protected website typically 60 to 90 minutes from time of initial capture. This report summarizes the SeaWiFS instrument capabilities, the protocol followed for automated near real-time processing, a physical basis for the NRL enhancements, and specific examples of the products. It closes with a glimpse of the potential utility of these products from the perspective of the warfighter.

FINDINGS AND RECOMMENDATIONS

It has been demonstrated that the SeaWiFS instrument has significant potential to benefit the warfighter through its ability to provide high resolution (1.1 km) visible imagery of atmospheric dust outbreaks with enhancements for optically thin regimes, as well as other meteorological/land-surface features of interest (e.g., clouds, fires, snow cover). Based on these findings, NRL and Fleet Numerical Meteorology and Oceanography Center (FNMOC) have collaborated to host a subset of these products upon the FNMOC Secure Internet (SIPRNET) beta-webpage for the purpose of i) making this new technology available to the warfighter, and ii) receiving feedback useful for improving its utility. It is recommended that the Navy continue to pursue the procurement of all telemetries having true color imaging capability to address the poor temporal resolution inherent to the polar orbiter platform. In this capacity, imagery from MODIS, OCM, and FY-1C are obvious candidates, with the former two requiring X-band receiving stations.

SeaWiFS True Color, Vegetation, and Dust Enhancement Processing at NRL Monterey

INTRODUCTION

The Satellite Meteorological Applications Section (Code 7541) at the Naval Research Laboratory (NRL) in Monterey has developed true color, vegetation enhancement, and airborne sand/dust enhancement processing capabilities for the Sea-viewing Wide Field of View Sensor (SeaWiFS) instrument. These products are made in near real time (typically 60 to 90 minute latency from time of ingest at the receiving stations) using telemetries captured at Navy Regional Centers (NRCs) located in Spain (Rota), Bahrain, and Japan (Yokosuka), and populate a password-protected website for several predefined sectors within the general coverage regions of these centers. Presented here is an overview of the SeaWiFS sensor and its capabilities/limitations, a summary of the procedure, and the current processing architecture. Examples drawn from the archived database (automated processing of these data commenced August 8, 2001) are presented to illustrate their quality and potential operational utility.

SeaWiFS—A Technical Overview




Fig-1 -- The SeaWiFS sensor (left) and SeaStar platform (right)

Platform/Instrument Specifications

The SeaWiFS instrument (Firestone and Hooker, 1996), launched aboard an extended Pegasus rocket on August 1, 1997, is an 8-channel whiskbroom scanning radiometer featuring 8 narrowband (~ 20 nanometers (nm) wide) spectral channels centered at 412, 443, 490, 510, 555, 670, 765, and 865 nm wavelengths. Carried aboard the SeaStar spacecraft (see Figure 1), SeaWiFS follows a sun-synchronous (98.3° inclination, 705 kilometer (km) altitude above mean sea level (AMSL)) orbit with a local noon descending equatorial crossing time. It has a local-area-coverage (LAC) swath width of 2801 km (corresponding to a maximum scan angle of 58.3°) and a nominal spatial resolution of 1.1 km at nadir. Global Area Coverage (GAC) is also available at 4 km degraded resolution and a reduced 1502 km swath (data limited to 45° scan angle). The 10-bit digitized data are transmitted down to Earth at an L-band frequency of

1.70256 Gigahertz (GHz). The instrument scans across 1285 picture elements at a rate of 6 Hz. Typical High Resolution Picture Transmission (HRPT) station telemetries include typically 4000 to 5000 scan lines of data (depending on local topographical/anthropogenic obstructions), translating to 11-13 minutes of capture time from the nominal initial-capture time stamp on the filename.

The primary function of SeaWiFS is to detect and monitor ocean color. Specifically, it has been designed to retrieve the small component (~5% of total signal) of water leaving reflected radiance whose spectral signature provides useful information about ocean phytoplankton content (expressed in terms of chlorophyll-A retrievals). A varying along-track sensor tilt angle of $\pm 19.8^\circ$ is used to avoid regions of sun glint (specular reflection of the solar disk upon the ocean surface) where chlorophyll-A retrievals cannot be performed. The information obtained from such retrievals is valuable to marine research and industry interests. Applications include guidance to the fishing industry, diver visibility information, surface currents, physical oceanography, general marine biology, and climate impacts on the marine ecosystem (e.g., McClain *et al.*, [1995], and Gordon *et al.*, [2001]). While atmospheric constituents such as cloud, dust, and aerosol are considered as noise to ocean color algorithms, the current research regards these components as the signal of interest. This report describes how SeaWiFS data are applied to enhance atmospheric and surface features/phenomena.

Instrument Advantages

The main advantage provided by SeaWiFS over optical spectrum instruments flown on the geostationary (e.g., the Geostationary Operational Environmental Satellite (GOES) constellation, Meteosat 5,7, Geostationary Meteorological Satellite (GMS), and the Indian National Satellite System (INSAT)) and other polar orbiter (e.g., National Oceanographic and Atmospheric Administration (NOAA), Defense Meteorological Satellite Program (DMSP), and many others) platforms for the current application is its multiple narrowband visible channels that provide a true color imaging capability. The Moderate-resolution Imaging Spectroradiometer (MODIS; King *et al.*, [1992]) carried aboard Earth Observing Satellites (EOS) Terra and soon to be launched Aqua platforms also provides these channels and additional channels reaching into the infrared (36 channels between 0.4 and 14.4 μm). At the time of this writing, MODIS data are only available to NRL over the areas of interest to this study on a research basis at 2-week latency from the Goddard Space Flight Center (GSFC) archives. MODIS telemetry is transmitted at X-band (7-8.5 GHz) whereas Navy facilities currently are limited to receipt of L-band (1.7-2.5 GHz). Direct broadcast MODIS data have been made available via the internet from the Space Science and Engineering Center at the University of Madison, Wisconsin, at the following address: <http://eosdb.ssec.wisc.edu/modisdirect/>, courtesy of Dr. Liam Gumley of the Cooperative Institute for Meteorological Satellite Studies (CIMSS).

Instrument Limitations and Other Caveats

The main deficiencies of SeaWiFS in terms of 24-hour operational utility are its lack of infrared channels, its limited temporal resolution, and proprietary nature. Infrared data are useful for nighttime imaging, cloud particle size estimation, and airborne dust enhancement over land surfaces, among other uses. At mid to low latitudes, only one to three passes are available near local noon—providing at best a “snapshot” of the synoptic-scale situation on any given day. Captures are increasingly frequent at the higher latitudes owing to the orbital geometry. Typical captures for the regional centers currently processed are on the order of 2 to 3 per day. Thus,

SeaWiFS products are most useful when juxtaposed with geostationary data that offer the temporal information required to infer details of the atmospheric circulation.

Because SeaWiFS was built, launched, and operated by Orbital Sciences Corporation (OSC), the data are formally available to the general public on a research-only basis and are provided at cost. The National Aeronautics and Space Administration (NASA) has contracted with OSC for the research use of a 5-year data set commencing in September 1997. Researchers who have registered as authorized SeaWiFS user (registration at <http://seawifs.gsfc.nasa.gov/SEAWIFS.html>) are granted permission to obtain the data from the NASA SeaWiFS archive, approved NASA Space Act Agreement ground station, or authorized individual. As authorized receiving stations, the NRCs providing near-real-time LAC data for this research are covered under the existing agreement, with the only criterion being that NRL does not disseminate the LAC-derived products to the general public in near real-time.

Data Processing

Several options exist for processing the SeaWiFS telemetry, depending on the format of the data. The formats currently received at NRL are NASA Level-0 (L0; 10-bit Data Capture Facility frame-formatter files), with Terascan Data Format (TDF) (pre-calibrated and navigated) upon special request. Data from the NRCs are in NASA L0 format, and require several preprocessing steps to calibrate and navigate the data as described below. For reasons described further along, the current approach to creating SeaWiFS products is based on NASA L0 data and is independent of the Terascan software package. Several approaches have been iterated upon in arriving at the current procedure including various blended combinations of software packages—some more appropriate for rapid deployment to remote operational centers and others geared toward in-house processing with all the conveniences of locally available third party software. While the purpose of this report is to summarize the current approach, alternative options and their associated data/software requirements will be touched upon in passing.

Worth noting is that the Perl programming language (Wall *et al.*, [2000]), running on the Linux platform, was selected as the scripting language for automated processing of SeaWiFS data. Perl draws from the strengths of many popular scientific programming languages such as C++ and Fortran while enhancing on the capabilities of other standard shell scripting languages. The Perl scripts written in support of the current SeaWiFS processing perform the requisite secretarial operations of data retrieval, file and directory manipulation, execution and status monitoring of telemetry updating and data processing codes, dissemination of imagery products to the website, and general housekeeping. Perl remains the lone constant among all processing options discussed in this report.

SeaDAS Processing Option

One of the available SeaWiFS processing options is the GSFC SeaWiFS Data Analysis System (SeaDAS) software package (Fu *et al.*, [1998]), which was designed specifically for viewing and basic manipulation of SeaWiFS data. It uses an embedded runtime Interactive Data Language (IDL) license as its operating paradigm. The SeaDAS software is designed to operate on NASA L0, Level-1A (L1A; raw spacecraft and instrument telemetry retained with converted geo-location, instrument telemetry, and selected spacecraft telemetry appended), and Level-1B (L1B; sensor calibration applied to the data). L1A and L1B data are stored in Hierarchical Data Format (HDF). The software includes a graphical user interface enabling straightforward viewing and manipulation of the data, as well as command-line functions useful for incorporating into scripts as batch jobs. The SeaDAS package was used early on in this research to examine the

general utility of SeaWiFS data in terms of coverage and data quality before proceeding with customized application. While SeaDAS is not used in the current processing (in the interest of gaining a higher level of control over product display options), several functions were adopted from this package for conversion from NASA L0 to L1B HDF files and data correction. SeaDAS remains an extremely useful stand-alone tool for SeaWiFS data visualization, and is available via the Internet at <http://seadas.gsfc.nasa.gov>. The website includes versions of SeaDAS for several operating platforms and has a limited level of helpful online support.

The Currently Implemented Processing Scheme

A simple overview of the current processing flow is as follows: I) SeaWiFS LAC telemetry captured at an NRC site and converted immediately to NASA L0 formatted file, II) Data sent to the satellite data storage facility at Naval Oceanographic Center (NAVO) at Stennis Space Center in Mississippi via file transfer protocol (ftp) push, III) Data are pushed via ftp to NRL Monterey from NAVO, IV) A periodic local cron job searches for receipt of new files, and if found: V) SeaWiFS processing script commences to calibrate, clean, apply atmospheric corrections, and generate products, VI) Products are uploaded to a password protected NIPRNET website. Latency of near real-time products is generally on the order of 1.5 hours from time of ingest at the NRC site. The remainder of this section provides additional details on the steps outlined above.

NRC Stations

The mid-latitude NRCs included in the current NRL processing are Rota [36.63N, 6.34E], Bahrain: [26.16N, 50.39E], and Yokosuka [35.28N, 139.67E]. Each station captures SeaWiFS passes on or around its local noontime hours (1100—1400 Z for Rota, 0700—1000 Z for Bahrain, and 0130—0430 Z for Yokosuka). NRL receives the NASA L0 data from NAVO as Gnu-compressed files typically 1 hour after the nominal capture time. File sizes vary according to pass coverage, with typical values ranging from 20 to 80 Megabytes. The 55 Gigabyte hard drive currently used as a storage bay for raw data, algorithms, and products is sufficient for several months of online storage. All data are eventually archived to CDROM or tape storage in a hierarchical structure partitioned by station, year, month and day.

Data Calibration

A cron job launched every half hour initiates the processing of newly received SeaWiFS data. A loop over all files present in the ftp "receive directory" checks for any new and unprocessed data. If a new file has arrived, it is uncompressed and copied to the local storage drive for subsequent processing to L1B calibrated radiances (expressed in $\text{mW}/\text{cm}^2\text{-sr-}\mu\text{m}$). Binary executables taken from the SeaDAS software package are used for this purpose, and require an updated SeaStar ephemeris for correct earth location (SeaWiFS requirement of 1-pixel geolocation accuracy). These data are available at <ftp:samoa.gsfc.nasa.gov>, and are updated on the local system if the current elements file is found to be more than one day old. Any errors incurred during the uncompressing or calibration steps are reported to a log file and the script is exited gracefully.

Sector Definition and Noise Corrections

Upon completion of L1B processing, an IDL script for customization of the data is spawned. Latitude, longitude, sun/sensor geometry, and SeaWiFS channel variables are extracted from the HDF data. A table of pre-defined sectors for each station is included and readily

updated for new operational areas of interest or one-time case studies. Definition of these sectors is based on the specification of latitude/longitude boxes (lower left and upper right corners). Owing to the scanning geometry, regions near the edge of the swath suffer spatial resolution degradation. As a result, imagery for these pre-defined sectors may include only partial coverage at compromised quality. A minimum data check of 20% coverage over the sector in question is enforced prior to proceeding with the processing. To ensure that the optimal information content for every SeaWiFS pass is provided, a "floater" sector is included which selects a box data away from the swath edges (poor resolution) and the horizons (avoiding numerous scan line drop-outs). The trade off for high image quality is a random coverage area from pass to pass.




Fig-2 -- Raw SeaWiFS data from NRC station (left) and noise/line corrected equivalent (right)

Once the sector of interest has been defined (or loops over numerous sectors), an embedded loop over SeaWiFS channels is performed for corrections of pixel noise and line dropouts. Noisy pixels appear in the imagery as a "salt and pepper effect" owing to the presence of spurious very high or very low data values. Line dropouts appear in imagery as black scan lines devoid of data or filled with noise. These imperfections are present in the data due to a combination of possible hardware limitations/problems and clutter associated with nearby structures. Cleaning of the data is accomplished in two ways. Lines identified as dropouts are replaced by previous good scan lines (bad lines at the very beginning or end of a data stream are replaced by their nearest good neighbor). If multiple adjacent dropouts are present, the previously patched line is used once again. This correction loses its cosmetic effectiveness for large data gaps, but provides marked improvements in cases of spurious line dropouts. Noisy pixels, assumed to be spurious, are identified using a threshold based on the absolute values of pixel derivatives computed along a scan line. When flagged, they are replaced by an average of the two adjacent pixels on the same scan line. Noise pixels on the edges of lines are simply replaced by the value of their nearest neighbor. Figure 2 illustrates the result of corrections applied to a subsector of SeaWiFS data collected over the Alps. The overall effect of these bad line and pixel noise corrections is dramatic, and regarded as an essential step in the production of high-quality SeaWiFS imagery. Additional noise corrections (not yet implemented) may be required to correct pixels where one of the channels is missing data (but was not flagged by the noise threshold). This results in a magenta, yellow, or cyan-biased pixel values in the RGB products.

Atmospheric Corrections

The effects of atmospheric molecular (sometimes referred to as "Rayleigh") scattering must be removed from the data before creation of true color products. The amount of Rayleigh scatter is proportional to λ^{-4} (wavelength) and hence is strongest for the shorter (e.g., blue, violet)

wavelengths. If left uncorrected it will manifest in the imagery as a semi-transparent milky blue haze increasing in opacity toward the edges of the swath (as higher sensor angles peer through an optically thicker atmospheric path), detracting from image contrast and clarity. To remove this undesirable component of the satellite signal, we use a radiative transfer model (Miller *et al.*, [2000]) to simulate the clear sky Rayleigh scatter over a dark surface as a function of the solar zenith, satellite zenith, and solar-satellite relative azimuth angles. Pre-calculated look-up tables were created for each SeaWiFS channel and the correction was applied on a pixel-by-pixel basis, provided the sun/satellite geometry in the Level 1B data. The primary caveat associated with this correction is the assumption of a cloud-free Rayleigh contribution that in some instances may result in an over-correction of pixels containing high clouds near the edges of the swath. Visual inspection of imagery has not indicated a significant distortion owing to this effect, however. Regions near the edge of the SeaWiFS swath should in general be interpreted with cautious regard to the possible distortions owing to larger atmospheric path lengths, three-dimensional effects (parallax), and possible bow-tie effects.

Scaling

Once the data have been calibrated, cleaned of noise, and corrected for Rayleigh scatter, the spectral radiances (I_λ) are converted to equivalent isotropic reflectances (R_λ) according to the simple relationship:

$$R_\lambda = \frac{\pi I_\lambda}{\mu_o F_{o,\lambda}}, \quad (1)$$

where μ_o is the cosine of the solar zenith angle and F_o is the solar spectral flux at wavelength λ . By definition, the isotropic reflectance represents the reflectance produced by an equivalent lambertian surface, and varies from 0.0 to 1.0. Any spurious values greater than 1.0 or less than 0.0 are thresholded by these upper and lower bounds. The reflectances are scaled by \log_{10} in an attempt to equalize the imagery and prevent the very bright cloud/snow pixels from dominating the information content of the products. These scaled reflectances are byte-scaled over the 256-element color table range of the IDL palette, with a minimum logarithmic reflectance of -1.65 mapped to the minimum saturation value (0) and 0.0 mapped to the maximum (255).

The scaled data are warped to a mercator projection corresponding to the sector of interest. This procedure is currently the most computationally time-consuming component of the processing, and options for optimization or alternative approaches are currently being explored. A segmentation fault error discovered in the IDL "map patch" command was discovered during this development and is currently being investigated by Research Systems Incorporated (RSI). Resolving this possible code problem may provide additional computational efficiency to the current code.

The final image products are created as jpegs at 80% of full quality. File sizes range from 200 to 800 Kilobytes depending on the sector and image information content. The true color, vegetation enhancement, and dust enhancement products for various stations and subsectors are copied to a password-protected online holding directory on the NRL Satellite Meteorology web page (http://kauai.nrlmry.navy.mil/sat_products.html).

Product Examples

True Color Enhancement

To produce the true color images, the blue (412 nm), green (555 nm), and red (670 nm) SeaWiFS data are loaded into the respective blue, green, and red IDL "color guns." The data comprise a single matrix of dimension (n,m,3) where n=along-scan direction and m=along-track direction. The resultant imagery is similar, but not identical, to what would be observed by the human eye from the vantage point of outer space; clouds as shades of gray to white, ocean surfaces as shades of blue, and land features as earth-tones and green in regions of heavier vegetation.

Examples of true color SeaWiFS imagery are shown for the Rota, Bahrain, and Yokosuka regional centers in Figures 3-5, respectively. Figure 3 demonstrates the immediate ease with which significant airborne dust is identified over oceans. The image depicts a widespread easterly plume of Saharan dust captured within the synoptic flow of a baroclinic system off the coast of Spain and Portugal. SeaWiFS is useful in monitoring these dust plumes as they migrate across the Atlantic Ocean (often reaching the eastern United States). The green colors in littoral regions of the Persian Gulf in Figure 4 correspond to a higher amount of bioactivity (e.g., plankton) in nutrient-rich waters. Cloud streets over land and evidence of biomass burning in the form of diffuse smoke plumes are apparent over Southeastern Asia in Figure 5. The NRC in Yokosuka also captures seasonal dust storms blowing off the Gobi desert. Owing to the general circulation of the atmosphere, large Gobi and Saharan dust storms may reach the continental United States (the former crossing the Pacific with the "Roaring Forties", and the latter crossing the Atlantic with the Tropical Trades). Implications of these teleconnections are discussed by Westphal *et al.* [1988], Prospero *et al.* [1987], and Prospero [1999].



Fig-3 -- SeaWiFS HRPT true color image of the Eastern Atlantic Ocean, Iberian Peninsula, and Northwestern Africa, captured by NRC in Rota, Spain (02/13/01, 1255Z). A large dust plume wrapping into a baroclinic system is indicated




Fig-4 -- SeaWiFS HRPT true color image of the Persian Gulf area, captured by NRC in Bahrain. Airborne dust is indicated. Phytoplankton is responsible for the green pigmentation in the littoral regions




Fig-5 -- SeaWiFS HRPT true color image of the Korean Peninsula, captured by NRC in Yokosuka Japan. Yellow arrows indicate areas of biomass smoke/pollution

Vegetation Enhancement

Because green vegetation possesses a relatively high albedo compared to soil in the "reflective" or shortwave infrared ($0.7\text{--}1.3\ \mu\text{m}$), a combined vis/shortwave-IR product that enhances vegetation regions is generated in a way similar to the true color enhancement described above. This vegetation enhancement product is similar to what has been produced for many years for land-use studies with Landsat TM data. The 670 nm (red) channel in the previously discussed RGB true color enhancement is replaced by the 865 nm (SeaWiFS channel 8) channel data. This results in green vegetation appearing as bright red and appears usually in sharp contrast to surrounding regions devoid of vegetation. An example of this product is shown in Figure 6. The vegetation enhancement may prove useful in identifying potential fetch areas for airborne dust.




Fig-6 -- True color (top) and vegetation enhancement (bottom). Bright red indicates regions with abundant plant life. Note seasonal changes in Fall vegetation compared against Summer (Figure 5)

Airborne Dust Enhancement

The detection and tracking of airborne dust from satellite has been a long-standing interest of the Navy and academia alike, and there is no shortage of papers treating the subject (e.g., Shenk and Curran [1974], Carlson [1978], Legrand et al. [1987], Lee [1989], Jankowiak and Tanre [1991], Tanre and Legrand [1991]). These earlier works made use of contrast and spectral signatures to identify and retrieve properties of dust against land and ocean backgrounds. An important capability of SeaWiFS, resulting from its multiple narrowband visible channels and indicated in the examples above, is discrimination between airborne dust and clouds/smoke via true color methods. Fine-grain particles lifted from sparsely vegetated and dry desert surfaces by strong frictional winds (typically greater than 10 m/s, usually by meso- and synoptic-scale circulation features) give rise to significant plumes of atmospheric dust. These plumes follow the low to mid-level atmospheric circulation and may also become incorporated within synoptic scale baroclinic systems (giving rise on occasion to unusually "mud rain" storms that have been reported to deposit a coating upon everything in their path).




Fig-7 -- Cartoon illustration of preferential absorption of blue light by dust plumes, resulting in yellow reflected light. Clouds scatter more uniformly over the visible wavelengths, resulting in white light

Perhaps more importantly to Navy interests, airborne dust has significant detrimental impacts on slant-range visibilities (with visible optical depths that can exceed 3.0 and accompanied by visibilities less than 1 nautical mile) and also poses a serious hazard in terms of its potential to damage turbine engines. This is of particular relevance to aircraft carrier operations in regions of the world prone to widespread dust outbreaks. Because airborne dust retains the earth tone hues (usually light brown or yellow, depending on the source region) of the underlying surface, it is readily identifiable in most cases from a true color image, especially for optically thicker dust plumes. For regions of less dust (where its effects on slant range visibility may still be appreciable), an additional enhancement beyond true color is required. NRL Monterey has developed a dust enhancement algorithm for SeaWiFS that attempts to provide this capability. Enhancement of dust is predicated on basic spectral properties that characterize its appearance at visible wavelengths. As indicated in Figure 7, yellow light (characteristic of many desert dust plumes) results from the removal of blue light (via preferential absorption by the dust, e.g., Patterson *et al.* 1977). This spectral contrast is even more dramatic between the blue and shortwave infrared channels. This preferential absorption does not occur to the same magnitude

in liquid/ice clouds (explaining why clouds appear as shades of gray to white, indicating nearly equal reflected intensities of red/green/blue light, in a true color composite). By defining a dust enhancement parameter " Δ ":

$$\Delta = \frac{\alpha_{865} - \alpha_{412}}{\alpha_{865} + \alpha_{412}},$$



where α_λ are reflectances at wavelength λ (nm), any dust component of the image will be enhanced. Cloud pixel values, which are relatively spectrally flat, will be diminished in brightness owing to the small numerator difference. The logarithm of the Δ parameter is scaled between -0.45 and 0.20 and loaded into the red channel of the RGB composite.

Owing to the significantly reduced red component for cloud pixels in the dust enhancement (small values of the Δ parameter) image, clouds typically appear as shades of light blue or cyan. Retaining the original gray/white cloud hues in the dust enhancement (for cosmetic purposes only) requires the implementation of a simple cloud mask—pixels flagged as cloudy can be re-assigned to their original red channel values. Clouds in the imagery are identified first by computing the mean scaled magnitude and standard deviation of the 412, 555, and 670 nm channels. Mean magnitudes exceeding 50% and standard deviation less than 2.5% are used as thresholds for positive cloud identification. The simple premise behind choosing these thresholds is that clouds are in general bright (high brightness magnitude) and relatively spectrally flat over the visible (low standard deviation). Pixels flagged as "cloudy" are reset to the red channel value in the Δ parameter. As the dust enhancement enhances land surfaces also, a land mask is applied to this product.

Figure 8 demonstrates the dust enhancement product covering the Persian Gulf region. The top panel pair reveals that while the true color imagery is useful in identifying the significant dust plumes, the dust enhancement reveals a far more extensive coverage of airborne dust circulating within the Gulf. The center and lower panel pairs further illustrate this enhancement capability. While not necessarily posing the same hazard to aircraft engines as the optically thick (bright) plumes, these areas of enhanced aerosol have detrimental impacts on slant-range visibility. Although more difficult to detect than over the oceans, the presence of significant dust over bright and/or sparsely vegetated land surfaces can in some cases be inferred by noting contrast reduction in the background terrain. The lack of an infrared channel on the SeaWiFS instrument precludes the technique of detecting elevated (cooler) dust above a warm surface background via emission measurements. The utility of EOS-MODIS, which provides 36 channels (including narrowband red, green blue, NIR and LWIR bands), will be explored in this capacity.

SeaWiFS BHR 2001/09/09 08497 Naval Research Lab My True Color
(Masked Ocean, 4127/7865x4127, Enhanced, Masked, 17mm)

SeaWiFS BHR 2001/09/09 08511 Naval Research Lab My Significant Dust Enhancement
(Masked Ocean, 4127/7865x4127, Enhanced, Masked, 17mm)



WHILE OPERATING IN THE AG IN SUPPORT OF OPERATION SOUTHERN WATCH (OSW) AND MARITIME INTERDICTION OPERATIONS (MIO), SHAMAL WINDS DECREASED VISIBILITY ON TWO OCCASIONS DUE TO BLOWING DUST AND SAND FROM SE IRAQ AND KUWAIT INTO THE NORTHERN ARABIAN GULF (NAG). DURING THESE EVENTS, VISIBILITY DROPPED TO 1 TO 3 MILES AND IMPACTED STRIKE OPERATIONS AS TARGETS BECAME OBSCURED.
--METOC Post Deployment Report

SeaWiFS BHR 2001/10/14 08497 Naval Research Lab My True Color
(Masked Ocean, 4127/7865x4127, Enhanced, Masked, 17mm)

SeaWiFS BHR 2001/10/14 08497 Naval Research Lab My Significant Dust Enhancement
(Masked Ocean, 4127/7865x4127, Enhanced, Masked, 17mm)



SeaWiFS BHR 2001/11/03 08127 Naval Research Lab My True Color
(Masked Ocean, 4127/7865x4127, Enhanced, Masked, 17mm)

SeaWiFS BHR 2001/11/03 08127 Naval Research Lab My Significant Dust Enhancement
(Masked Ocean, 4127/7865x4127, Enhanced, Masked, 17mm)




Fig-8 -- Examples of airborne dust enhancements over the Persian Gulf. Optically thin dust plumes appear as darker tones of red. Land regions in the dust enhancement have been masked




Fig-9 -- Typhoon Pabuk makes landfall on Japan




Fig-10 -- SeaWiFS captures volcanic ash plume from Mt. Etna eruption. Land regions in the dust enhancement have been masked out

Other Utilities

The global coverage afforded by the polar orbiting platform provides SeaWiFS with opportunities to survey many atmospheric and terrestrial phenomena. Its utility as an additional sensor for tropical storm monitoring (e.g., Typhoon Pabuk shown in Figure 9) may increase in relevance in light of the current mechanical problems aboard the Geostationary Meteorological Satellite (currently providing coverage of the Tropical Western Pacific and the primary satellite observation platform supporting the Joint Typhoon Warning Center). Unexpected events provide unique opportunities to examine additional capabilities of the SeaWiFS channels. The eruption of Mt. Etna, shown in Figure 10, demonstrates an additional utility of the dust enhancement product—revealing features of the ash plume difficult or impossible to detect in panchromatic or even true color renditions. Depending on their composition and concentration (not all volcanic plumes are comprised of materials that will be enhanced by the currently detailed dust enhancement), such plumes may be tracked around the globe, providing invaluable guidance to the commercial airline industry for avoiding these potentially serious flight hazards. The detection capabilities of SeaWiFS offer a valuable asset to Volcanic Ash Advisory Centers (VAACs; e.g., <http://www.ssd.noaa.gov/VAAC/washington.html>) distributed world-wide whose charter is to monitor and track these plumes globally, and also the Geneva-based World Meteorological Organization (WMO; e.g., <http://www.wmo.ch/indexflash.html>), which coordinates global scientific activity among an international panel of participants.

Ongoing Developments

New Processing Formats

The SeaWiFS processing as outlined in this report is well suited for the creation and analysis of high quality SeaWiFS imagery products in an automated, near real-time framework. A Cooperative Research and Development Agreement (CRADA) exists between NRL Monterey and the SeaSpace Corporation (whereby a TeraScan license is provided in return for NRL-developed algorithms suitable for inclusion to the TeraScan processing suite). Furthermore, the NRCs mentioned in this report all use the TeraScan system as their ingest and processing platform.

For the reasons cited above, efforts to reproduce this processing in a fashion entirely independent of third party software have resulted in an analogous package that assumes receipt of SeaWiFS data in TeraScan Data Format and proceeds to customize the data in the FORTRAN-90 programming language. True color and dust enhancement image rendering is then completed using the "rgbimage" TeraScan intrinsic function. This FORTRAN-based version is actually more efficient and hence runs faster than its IDL counterpart. It is currently being tested for robustness in anticipation of transition to operational use. Until an HDF-to-TDF converter is written that is capable of handling the multiple sensor zenith angle settings characteristic of the SeaWiFS sensor (or the data stream changes from LO to TDF), the default NRL Monterey in-house processing will likely remain IDL-based.

Blended Products

SeaWiFS is only one of several telemetries available for processing at NRL Monterey. It is a straightforward procedure to incorporate data from these other sensors within the same image to produce a multi-sensor product. For example, the masked-out land areas in the dust enhancement product may be filled in by temporally matched geostationary data (e.g., Meteosat 5 over Bahrain, MeteoSat 7 over Rota, and GMS over Yokosuka). Infrared information can be used to enhance regions of elevated dust over the land in certain situations. As NRL also has at

its disposal analysis and forecast data from its mesoscale (Coupled Ocean-Atmosphere Mesoscale Prediction System)TM and global scale (Navy Operation Global Atmospheric Prediction System) models, it may also prove useful to blend these data into the products. Using again the example of the dust enhancement product, inclusion of the COAMPSTM 925 mb wind field in the form of vectors overlaid upon the imagery may serve not only as a qualitative validation of the model analysis but also provide the METOC officer in the field with a means to predicting the migratory behavior of significant dust plumes in the short term. Overlay of short-term forecasts of the frictional wind over land (winds near the surface that are responsible for lifting the dust into the atmosphere) may also be of use. Of course, any such multi-sensor and model-fusion products will require a training module identifying the various components, strengths, and weaknesses.


These data are of immediate relevance to both the initialization and validation of the Navy Aerosol Analysis and Prediction System (NAAPS; a global, multi-component analysis and modeling capability to produce aerosol products from satellite data and surface-based measurements). The goal of NAAPS is to improve the forecasting/nowcasting of visibility restrictions caused by aerosols, including dust, smoke, and volcanic ash. Information and forecast products associated with NAAPS may be found at <http://www.nrlmry.navy.mil/aerosol>.

The image products discussed in this report are intended for use in the field by Navy METOC officers for at-a-glance identification of dust storms and/or other features of interest; they are qualitative in nature. In other words, these products should not be misinterpreted as providing a quantitative flag for delineating the scene for dust or other constituents. Quantitative aerosol optical properties and associated slant-range visibility products are retrievable from SeaWiFS channels. Although the topic of aerosol retrievals is beyond the scope of the current work, extensive work in this area by several colleagues at NRL Monterey (D. Westphal, P. Flatau, K. Richardson, A. Kuciauskas) and the Naval Postgraduate School (P. Durkee) is ongoing.

Extension to MODIS Processing

The MODIS instrument offers a similar true color imaging capability together with improved spatial resolution (up to a factor of 4 over SeaWiFS HRPT). Figure 11 provides an example of the MODIS dust enhancement over the Northern Arabian Sea. Plumes of dust over ocean and dry lakebeds on the desert interior (often serving as sources for dust) are enhanced as shades of pink. Of specific relevance to the dust enhancement product is the availability of thermal infrared channels that enable the discrimination of elevated (cooler) dust plumes over warm backgrounds. On-board calibration of MODIS radiances supports accurate physical retrievals of aerosol optical properties. A technique for producing 250m true color imagery using 500m blue/green and 250m red channels has also been developed. This high spatial resolution capability is enhanced by temporal coverage when considering the Terra (MODIS: 1030 descending node), SeaStar (SeaWiFS: 1200 descending node), and Aqua (MODIS: 1330 ascending node; platform to be launched in April 2002) platforms in concert. This quasi-geostationary 3-hour loop will provide valuable information on cloud and/or dust motion.

MODIS 10/10/2001 0635-Z NRL Monterey



WHILE OPERATING IN THE NAS IN SUPPORT OF OPERATION ENDURING FREEDOM (OEF), THE PRIMARY METOC-RELATED IMPACT TO OPERATIONS WAS DECREASED VISIBILITY IN N, W, AND S AFGHANISTAN DUE TO STRONG WINDS [...] IN ONE CASE, THE EXTENT OF THE SUSPENDED DUST AREA RANGED WELL OUT INTO THE NORTHERN ARABIAN SEA, WITH VISIBILITY LESS THAN 1 NM.
 --METOC Post Deployment Report

Fig-11 -- MODIS dust enhancement (0.5 km resolution) over the Northern Arabian Sea, true color over land. Dust over the ocean and dry lake beds appear as shades of pink. Accompanying text from Navy MetOc post deployment report corresponding to the storm observed in this image

Additional sensors with similar true color imaging capabilities (e.g., GLI and POLDER aboard ADEOS II, MISR aboard Terra, OSMI aboard KOMPSAT, OCM aboard OCEANSAT, FY-1C, TM/ETM aboard the Landsat series, etc.) would in some cases provide additional temporal information. The potential METOC benefit to the war fighter in terms of from these state of the art instruments cannot be understated.

Conclusion

A new processing capability for generation of true color, vegetation enhancement, and dust enhancement imagery from the 8-channel SeaWiFS instrument has been developed by the NRL Monterey Satellite Meteorology Applications Section team. Near real-time processing of telemetry captured from Navy Regional Centers in Rota, Bahrain, and Yokosuka currently populate the following password-protected website on the NRL Monterey satellite page at 1-2 hour latency:

http://kauai.nrlmry.navy.mil/archdat/swf_nrc/

A number of geo-fixed subsectors spanning the coverage zones for each of the centers have been defined, in addition to a "floater" sector that roams with the nadir-most pixels of any given SeaWiFS pass. Owing to the sensitivity of regions covered by these regional centers and the existing proprietary agreement with Orbimage, access to these products has been restricted to Navy METOC operational purposes. A preliminary agreement has been reached with Fleet Numerical Meteorology and Oceanography Center (FNMOC) to host the products upon their secure Internet website (SIPRNET) while NRL awaits procurement of its own SIPRNET capability. A number of other hosting options that would provide 24/7 support of the SeaWiFS product suite via secure protocol are currently being explored.

The relevance of high-resolution imagery to Navy operations in the context of aerosol/dust detection is evidenced by numerous METOC post-deployment reports. An excerpt from one such report, speaking to METOC-related problems affecting deployments during Operation Enduring Freedom (Afghanistan), is included below:

"On several occasions weapons laser lock was difficult due to blowing dust and sand, or low ceilings. Occurred primarily over N, C, and W Afghanistan. [...] successfully used high-res satellite imagery for short-term forecasts of blowing dust events in the AG. The three blowing dust events that resulted in mission cancellations were all accurately forecast."

-LCDR K. Schwingshaki, USS Enterprise, METOC Post Deployment Report

Perhaps the greatest testimony to the potential utility of these products has been provided in the form of feedback from METOC officers who have seen these products first-hand. The following recently received comments from METOC officers with specific regard to the NRL SeaWiFS products outlined in this report indicate a strong interest in obtaining real-time imagery onboard carriers for use in both plenary and tactical guidance:

"Imagery is fantastic—and very operationally useful"

-LCDR Ray Chartier, NSAWC METOC Officer, NPMOD Fallon

"Are these images on SIPR??? If so where...great stuff."

-LCDR Mike Angove, Staff Meteorologist/Oceanographer, Carrier Group Three

Two main points become clear from the above commentary: 1) SeaWiFS and other sensors offering true color imaging capability are of significant value and in high demand for Navy operations, and 2) in spite of the fact that such data has been available for some time now from the satellite platform (e.g., LandSat-TM) this capability has not been transitioned effectively to the end-users who require it (i.e., those deployed in the field). In turn, the twofold intent of this

report has been to demonstrate the current in-house processing capabilities for the SeaWiFS sensor and articulate this operational demand. A logical extension to these statements is that there exists a pressing need for X-band receiving stations in perennially sensitive regions of the world for the purpose of capturing MODIS and other high-data-rate (both multi- and hyper-spectral) satellite telemetries. The potential savings in terms of both loss of life and equipment (e.g., Cantu [2001] reports a 51 million dollars annual loss in Navy equipment attributed to visibility-related meteorological phenomena such as aerosols, dust, and atmospheric trapping layers) owing to improved METOC guidance gained from these state-of-the-art sensors far outweighs the one-time cost of the receiving stations themselves.

Acknowledgements

The support of the research sponsors, the Office of Naval Research (6.2) and the Oceanographer of the Navy through the program office Space and Naval Warfare Systems Command (PMW-155; 6.4), is gratefully acknowledged.

References

- Cantu, R. A., 2001: The role of weather in class A naval aviation mishaps FY90-98, M.S. Thesis, Naval Postgraduate School, Monterey, CA, 106pp.
- Carlson, T. N., 1978: Atmospheric turbidity in Saharan dust outbreaks as determined by analyses of satellite brightness data, *Mon. Weather Rev.*, **107**, 322-335.
- Firestone, E. R., and S. B. Hooker, 1996: *SeaWiFS Technical Report Series. Volume 36 – SeaWiFS Technical Report Series Cumulative Index: Volumes 1-35*, 36, Laboratory for Hydrospheric Processes, NASA Goddard Space Flight Center, Greenbelt, MD, 55pp.
- Fu, G., K. S. Baith, and C. R. McClain, 1998: SeaDAS: the SeaWiFS data analysis system, *Proc. of 4th Pacific Ocean Remote Sensing Conf.*, Qingdao, China, July 28-31, 1998, 73-79.
- Gordon, H. R., G. C., Boynton, W. M. Balch, S. B. Groom, D. S. Harbour, and T. J. Smyth, Retrieval of coccolithophore calcite concentration from SeaWiFS imagery, *Geophys. Res. Lett.*, **28**, 1587-1590.
- Jankowiak, I., and D. Tanre, 1992: Satellite climatology of Saharan dust outbreaks: method and preliminary results, *J. Climate*, **5**, 646-656.
- King, M. D., Y. J. Kaufman, W. P. Menzel, and D. Tanre, 1992: Remote sensing of cloud, aerosol and water vapor properties from the moderate resolution imaging spectrometer (MODIS), *IEEE Trans. Geoscience and Remote Sensing*, **30**, 2-26.
- Lee, T. F., 1989: Dust tracking using composite visible/IR images: a case study, *Weather and Forecasting*, **4**, 258-263.
- Legrand, M., M. Desbois, and K. Vovor, 1987: Satellite detection of Saharan dust: optimized imaging during nighttime, *J. Climate*, **1**, 256-264.
- McClain, C. R., et al., 1995: *NASA Technical Memorandum – SeaWiFS Technical Report Series*, **28**, Laboratory for Hydrospheric Processes, Goddard Space Flight Center, Greenbelt, MD, 38pp.
- Miller, S. D., G. L. Stephens, C. K. Drummond, A. K. Heidinger, and P. T. Partain, 2000: A multisensor diagnostic cloud property retrieval scheme, *J. Geophys. Res.*, **105**, No. D15, 19955-19971.
- Patterson, E. M., D. A. Gillette, and B. H. Stockton, 1977: Complex index of refraction between 300 and 700 nm for Saharan aerosols, *J. Geophys. Res.*, **82**, No. 21, 3153-3160.
- Prospero, J. M., 1999: Long-term measurements of the transport of African mineral dust to the southeastern United States: implications for regional air quality, *J. Geophys. Res.*, **104**, No. D13, 15917-15927.
- Prospero, J. M., R. T. Nees, and M. Uematsu, 1987: Deposition rate of particulate and dissolved aluminum derived from Saharan dust in precipitation at Miami, Florida, *J. Geophys. Res.*, **92**, 14723-14731.
- Shenk, W. E., and R. J. Curran, 1974: The detection of dust storms over land and water with satellite visible and infrared measurements, *Mon. Weather Rev.*, **102**, 830-837.
- Tanre, D., and M. Legrand, 1991: On the satellite retrieval of Saharan dust optical thickness over land: two different approaches, *J. Geophys. Res.*, **96**, No. D3, 5221-5227.
- Wall, L., T. Christiansen, and J. Orwant, 2000: *Programming Perl*, O'Reilly & Associates, Inc., Sebastopol, CA, 1067pp.
- Westphal, D. L., O. B. Toon, and T. N. Carlson, 1988: A case study of mobilization and transport of Saharan dust, *J. Atmos. Sci.*, **45**, 2145-2175.

```

# Call external software to process data (clean, remove rayleigh, scale)
print "Calling external processing software.\n";
system ("process_modis") == 0 or die "Problem with process_modis: $!";

##SNIPPET FROM process_modis_color.f90 PERTAINING TO DE**
#! 1) Atmospheric Correction (snippet)
# airmass = 1.0/mu_sun + 1.0/mu_sat
# trans_sat = exp(-1.0*ray_taus(i)/mu_sat)
# trans_sun = exp(-1.0*ray_taus(i)/mu_sun)
# tro = proc_chandat*pi/( F_sun_adj(i) * mu_sun * exp(-1.0*airmass*uoz*aoz(i))
# )
# trayu = ( (2.0/3.0 + mu_sat)+(2.0/3.0 - mu_sat)*trans_sat) / &
# ( 4.0/3.0 + ray_taus(i) )
# trayd = ( (2.0/3.0 + mu_sun)+(2.0/3.0 - mu_sun)*trans_sun) / &
# ( 4.0/3.0 + ray_taus(i) )
# tro = (tro-ray_ref)/( trayu*trayd*exp(-1.0*airmass*(ao2(i) + awv(i))) )
# proc_chandat = tro/(1.0+raysa(i)*tro) !units of reflectance [0-1]
#! 2) Truncate negative numbers to 0, if they occur
#! Truncate numbers greater than unity to unity, if they occur
# WHERE (proc_chandat < 0.0223) proc_chandat = 0.0223
# WHERE (proc_chandat > 1.0) proc_chandat = 1.0
#! 3) Scale the processed data if applicable
# print *, "Scaling the data by log_10"
# proc_chandat = LOG10(proc_chandat)
#! 4) Dust Enhancement
# print *, "Creating dust enhancement"
# WHERE ( ((chan03_dat+chan02_dat) > 0.0) .AND. (chan02_dat > 0.0223) )
# dust_enhance = (chan02_dat-chan03_dat)/(chan02_dat+chan03_dat)
# ELSEWHERE
# dust_enhance = -0.40
# ENDWHERE
#! 5) Truncate between desired values
# WHERE (dust_enhance < -0.40) dust_enhance = -0.40
# WHERE (dust_enhance > 0.15) dust_enhance = 0.15
####END SNIPPET###

#-----
# Dust Enhancement
#-----
if ($have_ir) {

print "Creating a \"dust enhanced\" image: ${OUTNAME}.dust1KM.$SECTOR.x.tiff\n";
###
# Water component
###
print "Doing ocean component...\n";

$min_blue_scl = -1.45;
$max_blue_scl = 0.0;
$min_green_scl = -1.45;
$max_green_scl = 0.0;
$min_de_scl = -0.40;
$max_de_scl = 0.15;

system ("emathp expr_vars='ref_469 ref_555 DE' num_exprs=3 ".
        "y1_expr='land ? $min_blue_scl : x1' ".
        "y2_expr='land ? $min_green_scl : x2' ").

```

```

"y3_expr='land ? $min_de_scl : x3' ".
"use_degrees= poly_size=100 box_sides='1 1' ".
"min_good='1' save_exprs='1 2 3' var_names='Blue_ocean Green_ocean
Red_ocean' ".
"var_units= var_types='float float float' scale_offsets= scale_factors=
".
"reflec_assem_$pid tmp_ocean_$pid") == 0 or die "Problem with emathp:
$!";

system ("imscale include_vars='Blue_ocean' image_colors=250 bg_color=250
bad_color=0 ".
"over_color=249 under_color=0 max_width=$SAMPLES max_height=$LINES
fixed_size=yes ".
"zoom_factor=1 real_resample=no est_range=no min_value=$min_blue_scl
max_value=$max_blue_scl invert_scale=no ".
"north_up=yes tmp_ocean_$pid tmp_blue_$pid") == 0 or die
"Problem occurred during imscale of blue ocean-component of dust
enhancement: $!";
system ("expim image_format=tiff image_var=Blue_ocean image_colors=250
color_palette=black-white ".
"draw_indexes= draw_names= tmp_blue_$pid blue_ocean.tiff_$pid") == 0 or
die
"Problem occurred during expim of blue_ocean.tiff_$pid creation: $!";

system ("imscale include_vars='Green_ocean' image_colors=250 bg_color=250
bad_color=0 ".
"over_color=249 under_color=0 max_width=$SAMPLES max_height=$LINES
fixed_size=yes ".
"zoom_factor=1 real_resample=no est_range=no min_value=$min_green_scl
max_value=$max_green_scl invert_scale=no ".
"north_up=yes tmp_ocean_$pid tmp_green_$pid") == 0 or die
"Problem occurred during imscale of green ocean-component of dust
enhancement: $!";
system ("expim image_format=tiff image_var=Green_ocean image_colors=250
color_palette=black-white ".
"draw_indexes= draw_names= tmp_green_$pid green_ocean.tiff_$pid") == 0
or die
"Problem occurred during expim of green_ocean.tiff_$pid creation: $!";

system ("imscale include_vars='Red_ocean' image_colors=250 bg_color=250
bad_color=0 ".
"over_color=249 under_color=0 max_width=$SAMPLES max_height=$LINES
fixed_size=yes ".
"zoom_factor=1 real_resample=no est_range=no min_value=$min_de_scl
max_value=$max_de_scl invert_scale=no ".
"north_up=yes tmp_ocean_$pid tmp_de_$pid") == 0 or die
"Problem occurred during imscale of red (DE) ocean-component of dust
enhancement: $!";
system ("expim image_format=tiff image_var=Red_ocean image_colors=250
color_palette=black-white ".
"draw_indexes= draw_names= tmp_de_$pid red_ocean.tiff_$pid") == 0 or die
"Problem occurred during expim of red_ocean.tiff_$pid creation: $!";

# Make RGB image
system ("tifftopnm red_ocean.tiff_$pid > red_ocean.ppm_$pid") == 0 or die
"Problem with tifftopnm call: $!";

```

```

system ("tifftopnm green_ocean.tiff_$pid > green_ocean.ppm_$pid") == 0 or die
"Problem with tifftopnm call: $!";
system ("tifftopnm blue_ocean.tiff_$pid > blue_ocean.ppm_$pid") == 0 or die
"Problem with tifftopnm call: $!";
system ("ppmtopgm red_ocean.ppm_$pid > red_ocean.pgm_$pid") == 0 or die
"Problem with ppmtopgm call: $!";
system ("ppmtopgm green_ocean.ppm_$pid > green_ocean.pgm_$pid") == 0 or die
"Problem with ppmtopgm call: $!";
system ("ppmtopgm blue_ocean.ppm_$pid > blue_ocean.pgm_$pid") == 0 or die
"Problem with ppmtopgm call: $!";
system ("rgb3toppm red_ocean.pgm $pid green_ocean.pgm $pid blue_ocean.pgm $pid
> tmp_ocean.ppm_$pid") == 0 or die "Problem with rgb3toppm call: $!";
system ("convert ppm:tmp_ocean.ppm_$pid tiff:tmp_ocean_one.tiff_$pid") == 0
or die "Problem occurred during convert of modis dust enhancement
product: $!";

```

```

###
# Sunlint mask
###
print "Making sunlint mask for use with dust enhancement imagery...\n";
$min_sunlint = 30.0;
$delta = 0.25;
system ("emathp expr_vars='sunlint ref_853' num_exprs=1 ".
        "y1_expr='land ? badval :
(x1<($min_sunlint+$delta))&&(x1>($min_sunlint-$delta)) ? ".
        "100 : (x1<($min_sunlint-$delta)) ? x2 : badval' ".
        "use_degrees= poly_size=100 box_sides='1 1' ".
        "min_good='1' save_exprs='1' var_names='glintmask' ".
        "var_units= var_types='float' scale_offsets= scale_factors= ".
        "reflec_assem_$pid tmp_glint1_$pid") == 0 or die "Problem with emathp:
$!";

```

```

system ("imscale include_vars='glintmask' image_colors=250 bg_color=250
bad_color=0 ".
        "over_color=252 under_color=2 max_width=$SAMPLES max_height=$LINES
fixed_size=yes ".
        "zoom_factor=1 real_resample=no est_range=no min_value=$min_green_scl
max_value=$max_green_scl invert_scale=no ".
        "north_up=yes tmp_glint1_$pid tmp_glint_$pid") == 0 or die
"Problem occurred during imscale of green ocean-component of dust
enhancement: $!";

```

```

system ("expim image_format=tiff image_var=glintmask image_colors=250
color_palette=black-white ".
        "draw_indexes='252' draw_names='yellow' tmp_glint_$pid
tmp_glint.tiff_$pid") == 0 or die
"Problem occurred during expim of tmp_glint.tiff_$pid creation: $!";

```

```

# Merge Sunlint Mask and Ocean image
system ("imgmerge background_file=tmp_ocean_one.tiff_$pid
foreground_file=tmp_glint.tiff_$pid clear_color=black ".
        "output_format=tiff tmp_ocean.tiff_$pid") == 0 or die "Problem with
imgmerge: $!";

```

```

###
# Land component
###

```

```

print "Doing land component...\n";
####
$min_blue_scl = -1.45;
$max_blue_scl = 0.0;
$min_green_scl = -1.45;
$max_green_scl = 0.0;
$min_red_scl = 1.30;
$max_red_scl = 2.70;
$min_rmb_lnd = -0.10;
$max_rmb_lnd = 0.25;
@stat = `stats include_vars=modis_ch31 printout=no reflec_assem_$pid`;
@stat2 = split(/ +/, $stat[4]);
$min_31 = $stat2[3];
$max_31 = $stat2[4];
print "Modis ch31 has min value of $min_31 and max of $max_31\n";
$max_irlnd = $max_31;
if ($max_irlnd < 28.0) {
    $min_irlnd = $max_irlnd-21.0;
} else {
    $min_irlnd = $max_irlnd/4.0;
}
print "...setting min_irlnd = $min_irlnd, max_irlnd = $max_irlnd\n";
# Should make fmf limits dynamic
$min_fmflnd = -2.0;
$max_fmflnd = 2.0;
$min_rmb_ir_diff = -1.5;
$max_rmb_ir_diff = 0.25;
$min_ch26 = 5.0;
####

system ("emathp expr_vars='ref_469 ref_555 ref_645 ref_853 modis_ch26
modis_ch31 modis_ch32' num_exprs=10 ").
    "y1_expr='land && ! bad(x6)? pow(10,x3)-pow(10,x1) : badval' ".
    "y2_expr='land && ! bad(x6)? pow(10,x2)-pow(10,x3) : badval' ".
    "y3_expr='land && ! bad(x6)? y1-y2 : badval' ".
    "y4_expr='land && ! bad(x6)? (x6>$max_irlnd) ? $max_irlnd :
(x6<$min_irlnd) ? $min_irlnd : x6 : badval' ".
    "y5_expr='land && ! bad(x6)? (y4-$min_irlnd)/($max_irlnd-$min_irlnd) :
badval' ".
    "y6_expr='land && ! bad(x6)? ((y3-y5)-
$min_rmb_ir_diff)/($max_rmb_ir_diff-$min_rmb_ir_diff) : badval' ".
    "y7_expr='x7-x6' ".
    "y8_expr='land && ! bad(x6)? (y7>$max_fmflnd) ? $max_fmflnd :
(y7<$min_fmflnd) ? $min_fmflnd : y7 : badval' ".
    "y9_expr='(y8-$min_fmflnd)/($max_fmflnd-$min_fmflnd)' ".
    "y10_expr='land && ! bad(x6)? (x5>$min_ch26) ? 1.0 : 0.0 : badval' ".
    "use_degrees= poly_size=100 box_sides='1 1' ".
    "min_good='1' save_exprs='1 2 3 4 5 6 7 8 9 10' ".
    "var_names='red_blu_diff grn_red_diff y1_y2_diff ir_trunc ir_norm
y3_y5_diff fmf fmf_trunc fmf_norm wv26_norm' ".
    "var_units= var_types='float float float float float float float float
float float' scale_offsets= scale_factors= ".
    "reflec_assem_$pid rmb_ir_landdiff_$pid" == 0 or die "Problem with
emathp: $!";

system ("copyvar include_vars='y3_y5_diff fmf_norm wv26_norm ir_norm'
overwrite_vars=n ").

```

```
"rmb_ir_landdiff_$pid reflc_assem_$pid") == 0 or die "Problem with
copyvar: $!";
```

```
$min_topo = 3000.0;
$stopo_scale = 3000.0;
system ("emathp expr_vars='ref_469 ref_555 y3_y5_diff fmf_norm wv26_norm
modis_ch03 ir_norm elevation' num_exprs=3 ".
    "y1_expr='land && ! bad(x6) ? x1 : badval' ".
    "y2_expr='land && ! bad(x6) ? x2 : badval' ".
    "y3_expr='land && ! bad(x6) ? (x8>$min_topo) ? x3+x4-x5+(1.0-x7)-
x8/$stopo_scale: x3+x4-x5+(1.0-x7) : badval' ".
    "use_degrees= poly_size=100 box_sides='1 1' ".
    "min_good='1' save_exprs='1 2 3' var_names='Blue_land Green_land
Red_land' ".
    "var_units= var_types='float float float' scale_offsets= scale_factors=
".
    "reflc_assem_$pid tmp_land_$pid") == 0 or die "Problem with emathp:
$!";
```

```
system ("emathp expr_vars='Red_land' num_exprs=1 ".
    "y1_expr='land ? x1 : $min_red_scl' ".
    "use_degrees= poly_size=100 box_sides='1 1' ".
    "min_good='1' save_exprs='1' var_names='Red_land' ".
    "var_units= var_types='float' scale_offsets= scale_factors= ".
    "tmp_land_$pid tmp_land_red_$pid") == 0 or die "Problem with emathp:
$!";
```

```
system ("copyvar include_vars='Red_land' overwrite_vars=yes ".
    "tmp_land_red_$pid tmp_land_$pid") == 0 or die "Problem with copyvar:
$!";
```

```
system ("imscale include_vars='Blue_land' image_colors=250 bg_color=250
bad_color=0 ".
    "over_color=249 under_color=0 max_width=$SAMPLES max_height=$LINES
fixed_size=yes ".
    "zoom_factor=1 real_resample=no est_range=no min_value=$min_blue_scl
max_value=$max_blue_scl invert_scale=no ".
    "north_up=yes tmp_land_$pid tmp_landblue_$pid") == 0 or die
    "Problem occurred during imscale of blue land-component of dust
enhancement: $!";
system ("expim image_format=tiff image_var=Blue_land image_colors=250
color_palette=black-white ".
    "draw_indexes= draw_names= tmp_landblue_$pid blue_land.tiff_$pid") == 0
or die
    "Problem occurred during expim of blue_land.tiff_$pid creation: $!";
```

```
system ("imscale include_vars='Green_land' image_colors=250 bg_color=250
bad_color= ".
    "over_color=249 under_color=0 max_width=$SAMPLES max_height=$LINES
fixed_size=yes ".
    "zoom_factor=1 real_resample=no est_range=no min_value=$min_green_scl
max_value=$max_green_scl invert_scale=no ".
    "north_up=yes tmp_land_$pid tmp_landgreen_$pid") == 0 or die
    "Problem occurred during imscale of green land-component of dust
enhancement: $!";
system ("expim image_format=tiff image_var=Green_land image_colors=250
color_palette=black-white ".
```

```

"draw_indexes= draw_names= tmp_landgreen_$pid green_land.tiff_$pid") ==
0 or die
"Problem occurred during expim of green_land.tiff_$pid creation: $!";

system ("imscale include_vars='Red_land' image_colors=250 bg_color=250
bad_color= ".
"over_color=249 under_color=0 max_width=$SAMPLES max_height=$LINES
fixed_size=yes ".
"zoom_factor=1 real_resample=no est_range=no min_value=$min_red_scl
max_value=$max_red_scl invert scale=no ".
"north_up=yes tmp_land_$pid tmp_landred_$pid") == 0 or die
"Problem occurred during imscale of red land-component of dust
enhancement: $!";
system ("expim image_format=tiff image_var=Red_land image_colors=250
color_palette=black-white ".
"draw_indexes= draw_names= tmp_landred_$pid red_land.tiff_$pid") == 0 or
die
"Problem occurred during expim of red_land.tiff_$pid creation: $!";

###
# Make RGB image
###
system ("tifftopnm red_land.tiff_$pid > red_land.ppm_$pid") == 0 or die
"Problem with tifftopnm call: $!";
system ("tifftopnm green_land.tiff_$pid > green_land.ppm_$pid") == 0 or die
"Problem with tifftopnm call: $!";
system ("tifftopnm blue_land.tiff_$pid > blue_land.ppm_$pid") == 0 or die
"Problem with tifftopnm call: $!";
system ("ppmtopgm red_land.ppm_$pid > red_land.pgm_$pid") == 0 or die "Problem
with ppmtopgm call: $!";
system ("ppmtopgm green_land.ppm_$pid > green_land.pgm_$pid") == 0 or die
"Problem with ppmtopgm call: $!";
system ("ppmtopgm blue_land.ppm_$pid > blue_land.pgm_$pid") == 0 or die
"Problem with ppmtopgm call: $!";
system ("rgb3toppm red_land.pgm_$pid green_land.pgm_$pid blue_land.pgm_$pid >
tmp_land.ppm_$pid") == 0
or die "Problem with rgb3toppm call: $!";
system ("convert ppm:tmp_land.ppm_$pid tiff:tmp_land.tiff_$pid") == 0
or die "Problem occurred during convert of modis dust enhancement
product: $!";

# Merge Ocean and Land RGB imagery, and metafile image
system ("imgmerge background_file=tmp_ocean.tiff_$pid
foreground_file=tmp_land.tiff_$pid clear_color=black ".
"output_format=tiff ${OUTNAME}.dust_tmp.tiff_$pid") == 0 or die "Problem
with imgmerge: $!";

system ("legend line_1=\"${satname}-MODIS $mm/$dd/$yyyy ${hhmm}-Z 1km Dust NRL
Monterey\" ".
"line_2=\"Pink=Possible Dust, Black/White=${min_sunglint}-Degree
Sunglint Zone\" line_3= text_height=$TEXT_HEIGHT text_type=bold line_offset=0
sample_offset=0 ".
"full_width=no center_text=no outline=yes solid_bg=yes $MASTER $LEGEND")
== 0
or die "Problem with legend: $!";

system ("xinject bg_var_name='master' colors_per=2 meta_colors='5 0 3 0 5 4' ".

```

```

"line_widths='2 1 2' line_types= marker_types= marker_sizes= ".
"image_colors=4 $MASTER $GRID $COAST $LEGEND meta.tdf_$pid") == 0
or die "Problem with xinject: $!";

system ("expim image_format=tiff image_var=master image_colors=4 ".
"color_palette=black-white draw_indexes=\"3 4 5 6\" ".
"draw_names=\"violet white blue salmon\" meta.tdf_$pid meta.tiff_$pid")
== 0
or die "Problem with expim: $!";

print "Merging composite with meta image...\n";
system ("imgmerge background_file=${OUTNAME}.dust_tmp.tiff_$pid
foreground_file=meta.tiff_$pid clear_color=black ".
"output_format=tiff ${OUTNAME}.dust1KM.${SECTOR}.x.tiff_$pid") == 0 or die
"Problem with imgmerge: $!";

# Adjust image quality
system ("convert -quality 80 tiff:${OUTNAME}.dust1KM.${SECTOR}.x.tiff_$pid ".
"jpeg:${OUTNAME}.dust1KM.${SECTOR}.x.jpg_$pid") == 0
or die "Problem occurred during convert of modis dust enhancement
product: $!";

```